

LÁNCKERÉK
előfűrt aggyal
görgős lánchoz
DIN 8187,
ISO 606 szerint

Anyaga: C45

$Z_e = 2,8 \text{ mm}$

$Z_z = 8,3 \text{ mm}$

Méret 8 x 3 mm			05B-1			05B-2					
z	D _a	D ₀	D _n	B _k	L _n	D _n	B _k	L _n			
8	24,0	20,90	13	6	12	12	8	18			
9	26,6	23,39	15	6	12	15	8	18			
10	29,2	25,89	17	8	12	17	8	18			
11	31,7	28,39	18	8	13	19	10	18			
12	34,2	30,91	23	8	13	24	10	18			
14	39,2	35,95	25	8	13	26	10	18			
15	41,7	38,48	28	8	13	29	10	18			
16	44,3	41,01	30	8	14	32	10	20			
17	46,8	43,53	30	8	14	34	10	20			
18	49,3	46,07	30	8	14	37	10	20			
19	51,9	48,61	30	8	14	39	10	20			
20	54,4	51,14	30	8	14	40	10	20			
21	57,0	53,68	35	8	14	40	10	20			
22	59,5	56,21	35	8	14	40	10	20			
23	62,0	58,75	35	8	14	40	10	20			
24	64,6	61,29	35	8	14	40	10	20			
25	67,5	63,83	35	8	14	40	10	20			
26	69,5	66,37	40	10	16	50	12	22			
27	72,2	68,91	40	10	16	50	12	22			
28	74,8	71,45	40	10	16	50	12	22			
29	77,3	73,99	40	10	16	50	12	22			
30	79,8	76,53	40	10	16	50	12	22			
31	82,4	79,08	40	10	16	60	12	22			
32	84,9	81,61	40	10	16	60	12	22			
33	87,5	84,16	40	10	16	60	12	22			
34	90,0	86,70	40	10	16	60	12	22			
35	92,5	89,25	40	10	16	60	12	22			
36	95,0	91,79	40	10	16	60	12	22			
37	97,6	94,33	40	10	16	60	12	22			
38	100,2	96,88	40	10	16	60	12	22			
39	102,7	99,42	40	10	16	60	12	22			
40	105,3	101,97	40	10	16	60	12	22			
45	118,0	114,69	60	12	20						
50	130,7	127,41	60	12	20						
57	148,6	145,22	80	14	20						
76	197,7	193,59	80	20	25						